

## Sentrius™ MG100 Gateway

Multi-wireless IoT gateway with LTE-M/NB-IoT and Bluetooth 5



### Features at a Glance

#### WIRELESS CONNECTIVITY

Gather data with long range Bluetooth 5 and then send it over low power LTE-M / NB-IoT cellular networks to the cloud.

#### CERTIFIED FOR DEPLOYMENT AROUND THE WORLD

Regulatory approvals for FCC (USA), ISED (Canada), EU, UKCA, and cellular approvals PTCRB, GCF, AT&T certifications with Verizon and Vodafone

#### CUSTOM APPLICATION DEVELOPMENT

Leverage the Sentrius MG100's sample application codebase to easily connect and send data to AWS or develop your own Zephyr applications.

#### PERSONAL SUPPORT AND SERVICES FOR YOUR IMPLEMENTATION

Laird Connectivity's Tier 2 and FAE support bring expert assistance to your integration, working with you and our engineering team to reduce your time to market.

Powered by Laird Connectivity's Pinnacle™ 100 Modem, the **Sentrius MG100 Gateway** captures data from Bluetooth 5 long range sensors and sends it to the cloud via a global low power cellular (LTE-M/NB-IoT) connection.



#### Get Started Quickly

The out-of-box starter kit solution includes Laird Connectivity's innovative Sentrius™ BT510 Bluetooth 5 Multi-Sensor platform, with Bluegrass Cloud portal for a seamless out of the box end to end solution for your PoC trial.

#### Custom Application Development

Leverage the power and simplicity of Zephyr RTOS programming on the integrated Cortex-M4F microcontroller to tailor your application specifically for your needs.

#### Flexible Power Options

Power the gateway with an external USB power supply with product options for a rechargeable backup battery in the event of a short-term power outage.

#### Antenna Choice

Use low-cost internal LTE and Bluetooth antennas or choose the external antenna variants to suit your application environment.

- LTE-M/NB-IoT radio via Sierra Wireless HL7800 module (Chipset: Altair ALT1250)
- LTE bands 1, 2, 3, 4, 5, 8, 12, 13, 20, 28
- Nordic nRF52840 – Bluetooth v5, Coded PHY (Long range), 1MPHY & 2MPHY support
- Onboard Cortex-M4F Microcontroller – 32-bit @ 64 MHz, 256 KB of RAM, 1 MB internal flash, 8 MB QSPI
- NFC Support and integrated antenna
- Certifications – FCC, ISED, EU, UKCA, Bluetooth SIG plus PTCRB, GCF and End Product certified – AT&T, Verizon, and Vodafone
- Flexible programming via Zephyr RTOS
- Antenna options – Unique integrated antenna variant plus external variant with SMA connectors
- Battery backup options for mains power outage needs
- Multi-purpose button and three configurable LEDs
- Compact form factor: 110.28 mm x 99.16 mm x 35.32 mm
- Customization – Custom branding, packaging, application development all available.



Bluetooth 5 Sensor Connectivity



Industrial IoT



Cold Chain Monitoring



Smart Buildings



Transportation

## SENTRIUS MG100 GATEWAY SPECIFICATIONS

<b>Wireless</b>	Bluetooth	<ul style="list-style-type: none"> <li>▪ Bluetooth 5.0 – Single mode</li> <li>▪ 4x Range (CODED PHY support) – Bluetooth 5.0</li> <li>▪ 2x Speed (2M PHY support) – Bluetooth 5.0</li> <li>▪ LE Advertising extensions – Bluetooth 5.0</li> <li>▪ Concurrent master, slave</li> <li>▪ BLE mesh capabilities</li> <li>▪ Diffie-Hellman based pairing (LE Secure Connections) – Bluetooth 4.2</li> <li>▪ Data packet length extension – Bluetooth 4.2</li> <li>▪ Link Layer Privacy (LE Privacy 1.2) – Bluetooth 4.2</li> <li>▪ LE Dual Mode Topology – Bluetooth 4.1</li> <li>▪ LE Ping – Bluetooth 4.1</li> </ul>
	Cellular	<ul style="list-style-type: none"> <li>▪ Multi-band cellular operation for world-wide operation</li> <li>▪ Category LTE M and category NB-IoT support</li> <li>▪ Power class 3</li> <li>▪ Sensitivity: LTE M: -105 dBm</li> <li>▪ Sensitivity: NB-IoT: -114 dBm</li> </ul>
<b>Compute</b>	MCU	Nordic nRF52840 Cortex-M4F
<b>Memory</b>	RAM	256 KB
	Onboard Flash	1 MB
	Additional Storage	SD card support ( <b>SD card not included</b> )
<b>External Interfaces</b>	USB	1x USB 2.0 Host
	SD Card	1x MicroSD slot (SDHC, SD Card 2.0) for additional external storage
<b>Physical</b>	Dimensions	110.28 mm x 99.16 mm x 35.32 mm
<b>Electrical</b>	Input Voltage	4.35-5.5V (standard USB power)
<b>Accelerometer</b>	Ultra-low power	Consumption down to 2 $\mu$ A
	Sensitivity	$\pm 2g/\pm 4g/\pm 8g/\pm 16g$ dynamically selectable full scale
	Input	I2C
<b>NFC</b>	Specification	13.56 MHz, Data rate 106 kbps, NFC Type2 and Type 4 tag emulation
<b>Temperature</b>	Operating Range	-40° to +80° C ( <i>non-battery backup version</i> )
<b>Power</b>		Lithium Ion 18650 size
	Battery Backup	2600 mAh standard capacity
		Built-in protection circuit module (PCM)
<b>Certifications</b>	Regulatory	FCC (US), ISED (Canada), EU (Europe), UKCA (UK)
	Industry	PTCRB, GCF
	Carrier	AT&T (complete), Verizon, and Vodafone

## Ordering a Sentrius MG100

### Micro-Gateways

PART NUMBER	DESCRIPTION
450-00011-K1	Sentrius MG100 micro gateway, LTE-M & NB1 modem, Bluetooth LE, MVNO SIM
450-00038-K1	Sentrius MG100 micro gateway, LTE-M & NB1 modem, Bluetooth LE, battery backup, MVNO SIM
450-00039-K1	Sentrius MG100 micro gateway, LTE-M & NB1 modem, Bluetooth LE, external antenna, MVNO SIM
450-00054-K1	Sentrius MG100 micro gateway, LTE-M & NB1 modem, Bluetooth LE, external antenna, battery backup, MVNO SIM

### Power Supplies

PART NUMBER	DESCRIPTION
223-00010	AC Adapter, 5V-2A, US, five-pin micro-B USB plug
223-00011	AC Adapter, 5V-2A, EU, five-pin micro-B USB plug
223-00012	Adapter, 5V-2A, UK, five-pin micro-B USB plug



## Laird Connectivity's Sentrius™ MG100 - Wireless IoT Starter Kit

Everything you need in one box to start your wireless IoT proof-of-concept in minutes

### Contains:

- 1 x Sentrius MG100 Micro Gateway, LTE-M & NB1 modem, Bluetooth LE, external antenna, battery backup, MVNO SIM
- 3 x Sentrius™ BT510 – Bluetooth 5 multi sensor, IP67 – temperature, shock/movement, and open/close contact
- 3 x Regional power supplies (US/EU/UK)

### Use Cases:

- Cold chain transportation monitoring
- Predictive Maintenance
- Industrial IoT
- Discover the power of Bluetooth 5, long-range battery-powered sensors

DESCRIPTION	PART NUMBER
455-00120 - Kit, Starter, Sentrius MG100 Micro Gateway & BT510	455-00120