

# 10 W DC-DC Converter P10E-Series



PHI-CON

- Wide 2:1 input range
- 1500 V<sub>DC</sub> isolation
- MTBF > 1 Mio. h
- Continuous short circuit protection
- Over current protection



## Model guide

Type	Input voltage		Input current		Output voltage [V <sub>DC</sub> ] nom.	Output current		Efficiency [%] typ.	Capacitor load (see 1) [mA] max.
	Nominal [V <sub>DC</sub> ]	Range [V <sub>DC</sub> ]	No load [mA] max.	Full load [mA] typ.		[mA] min.	[mA] max.		
<b>Single output</b>									
P10E122R5S	12	9...18	10	790	2.5	0	3000	81	2200
P10E123R3S	12	9...18	10	1005	3.3	0	3000	84	2200
P10E1205S	12	9...18	10	990	5.0	0	2000	86	2200
P10E1212S	12	9...18	10	980	12.0	0	833	87	820
P10E1215S	12	9...18	10	960	15.0	0	667	89	470
P10E242R5S	24	18...36	10	380	2.5	0	3000	84	2200
P10E243R3S	24	18...36	10	495	3.3	0	3000	85	2200
P10E2405S	24	18...36	10	480	5.0	0	2000	89	2200
P10E2412S	24	18...36	10	485	12.0	0	833	88	820
P10E2415S	24	18...36	10	485	15.0	0	667	88	470
P10E482R5S	48	36...75	10	190	2.5	0	3000	84	2200
P10E483R3S	48	36...75	10	250	3.3	0	3000	85	2200
P10E4805S	48	36...75	10	240	5.0	0	2000	88	2200
P10E4812S	48	36...75	10	245	12.0	0	833	87	820
P10E4815S	48	36...75	10	240	15.0	0	667	88	470
<b>Dual output</b>									
P10E1212D	12	9...18	10	980	±12.0	0	±416	87	2 x 220
P10E1215D	12	9...18	10	970	±15.0	0	±333	88	2 x 150
P10E2412D	24	18...36	10	485	±12.0	0	±416	88	2 x 220
P10E2415D	24	18...36	10	475	±15.0	0	±333	90	2 x 150
P10E4812D	48	36...75	10	245	±12.0	0	±416	87	2 x 220
P10E4815D	48	36...75	10	245	±15.0	0	±333	87	2 x 150

## Specifications

<b>Input</b>	
Filter	Pi Network
Reflected input ripple current	20 mA <sub>p-p</sub> (Figure 1)
Start up time	20 ms, typ.
<b>Isolation:</b>	
In / Out Rated voltage (60 s)	1500 V <sub>DC</sub> , Standard
Input or output to case	1000 V <sub>DC</sub>
Resistance	10 <sup>9</sup> Ω
Capacitance	1000 pF, typ.
<b>Output</b>	
Voltage accuracy	± 1 %
Line regulation	± 0.5 %, max.
Load regulation @ 0...100 % load change	± 0.5 % @ P10ExxxxS ± 1% @ P10ExxxxD & P10Exx3R3x
Over current protection	150 %, typ. of max. current
Short circuit protection	Continuous (automatic restart)
Ripple and noise (at 20 MHz BW)	75 mV <sub>p-p</sub> , max.
Dual output cross deviation @ 75 % load difference	5 %, max.
Temperature coefficient	± 0.02 % / °C
Transient recovery time	200 μs, typ. @ 25 % load steps
<b>Output over voltage protection, Z-diode clamping</b>	
P10Exx2R5S, P10Exx3R3S	3.9 V
P10Exx05S	6.2 V
P10Exx12x	15 V
P10Exx15x	18 V
<b>General</b>	
Switching frequency	330 kHz, typ.
Safety standards	IEC, EN, UL, cUL60950-1 IEC, EN, UL, cUL62368-1
Reliability calc. MTBF (MIL-HDBK-217F)	1 Mio. h @ Ta 25 °C

<b>EMC specifications</b>	
Radiated emissions	EN55032 Class A
Conducted emissions	EN55032 Class A (see Fig. 3)
ESD	IEC61000-4-2 perf. criteria A
RS	IEC61000-4-3 perf. criteria A
EFT (see Fig. 3)	IEC61000-4-4 perf. criteria A
Surge (see Fig. 3)	IEC61000-4-5 perf. criteria A
CS	IEC61000-4-6 perf. criteria A
PFMF	IEC61000-4-8 perf. criteria A
<b>Environmental</b>	
Operating ambient temperature	-40 ... 85 °C
Case temperature	100 °C, max.
Storage temperature	-40 ... 125 °C
Derating	See SOA diagram
Humidity	95 % max., non condensing
Cooling	Air convection 30...60 LFM
<b>Physical</b>	
Weight	17 g
Potting material	Epoxy (UL94V-0 rated)
Case material	Nickel coated copper
<b>Absolute maximum ratings</b>	
Input voltage < 100 ms	
P10E12xxx	25 V <sub>DC</sub>
P10E24xxx	50 V <sub>DC</sub>
P10E48xxx	100 V <sub>DC</sub>
Lead soldering Temperature	260 °C for 10 s, distance from package 1.5 mm

# 10 W DC-DC Converter P10E-Series

1. Specified by nominal in voltage and constant resistive load.
2. Parallel operation of DC/DC-Converter outputs is not recommendet.
3. The P10E-series is not usable in IGBT and MOSFET driver applications.

Figure 1 Measure circuit input reflected ripple current




Figure 2 Measure circuit output ripple & noise voltage





Figure 3











Application circuit to meet EFT IEC61000-4-4 class A, Surge IEC61000-4-5 class A and EMI conducted emission EN55032 Class A






PHI-CON

# 10 W DC-DC Converter P10E-Series




# 10 W DC-DC Converter P10E-Series

## Dimensions





All units in mm

1. Pin diameter tolerance  $\pm 0.05$  mm
2. Pin pitch tolerance  $\pm 0.35$  mm
3. Case tolerance  $\pm 0.5$  mm



Pin assignment		
Pin	Single	Dual
2	-V Input	-V Input
3	-V Input	-V Input
9	No Pin	Common
11	Not Connected.	-V Output
14	+V Output	+V Output
16	-V Output	Common
22	+V Input	+V Input
23	+V Input	+V Input



PHI-CON is a trademark of HY-LINE Holding GmbH.

Only for professional use by professionals! Not for resale or distribution to the general public in any way! Read the instructions carefully before using!

**Life Support Policy:** HY-LINE does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user. Rev: 20171108 f